

### **White Sand Prime EP20**

**Multipurpose Solvent-containing Epoxy Primer** 

## **Description**

White Sand Prime EP20 two-component, solvent-containing, low viscosity epoxy resin-based primer, used as a primer for concrete surfaces.

It is commonly utilized as part of complete system in conjunction of other WHITE SAND products.

# **Uses and Key Functions**

Used for priming normal to strong absorbent concrete substrates.

### **Features and Advantages**

- Easy Application.
- Multipurpose Functions.
- Low viscosity.
- Excellent bond strength.
- Good penetration.

### **Product Performance Properties**

Туре	Epoxy-based solvent containing primer
Mix Ratio	Factory proportioned
Solid Content	50 % (volume)
Pot Life	40 minutes (at 23 C)
Dry to touch	4 – 10 hours (at 23 C)
Open Time	4 – 16 hours
Full Cure	7 days (at 23 C)
Coverage	15 m2/liter approx

# **Directions for Use**

#### **Substrate Preparation**

All surfaces to receive White Sand Prime EP20 should be structurally sound, dry, clean and free of surface contaminants.

Proper surface preparation is an extremely important factor in the immediate and long-term successful performance of applied epoxy system.

New concrete must be at least 4 weeks old and have a moisture content not more than 5%.



### **Mixing**

Pour the entire content of the hardener container into the base container (the base container is oversized to allow for easy mixing). Mix thoroughly with a low speed jiffy blade for 3 minutes until the material becomes uniform and even in consistency.

To ensure proper system cure and performance, avoid to mix part packs, and do not add solvent at any stage.

#### **Application**

Apply the mixed White Sand Prime EP20 uniformly to the prepared substrate using brush or lambs-wool roller or squeegee, at a spread rate of about 15 m2/liter. Take care not to puddle the material, and ensure even coverage. Note: material left in the pail will generate heat and have a reduced pot life.

Once primer has become tacky to the touch, proceed to installation of epoxy flooring, or repair system.

Note: primed surface should be recoated within the open of the primer.

### **Packaging**

4.0 liters pack.

#### Coverage

4.0 liters pack of White Sand Prime EP20 cover 60 m2 in a single coat. This is an approximate spread rate given for estimating purpose only.

#### **Storage and Shelf Life**

White Sand Prime EP20 components have a minimum shelf life of 12 months when stored in dry warehouse conditions, in unopened and undamaged original packaging. If stored in high temperatures, and/or high humidity conditions, the shelf life may be reduced.

#### **Storage and Shelf Life**

White Sand Prime EP20 components have a minimum shelf life of 12 months when stored in dry warehouse conditions, in unopened and undamaged original packaging. If stored in high temperatures, and/or high humidity conditions, the shelf life may be reduced.

### **Safety Precautions**

The two components of White Sand Prime EP20 are flammable material. Do not expose to naked flames or other sourced of ignition. Containers should be tightly sealed when not in use. In the event of fire, extinguish with carbon dioxide or foam.

White Sand Prime EP20 should not come in contact with skin or eyes. Avoid prolonged inhalation of vapors. Some people are sensitive to epoxy resin, hardeners, and solvents. Gloves, goggles and barrier cream should therefore be used.

Ensure adequate ventilation, and if work in enclosed areas, suitable breathing apparatus is recommended. If mixed material comes in contact with skin, it must be removed before it hardens with a resin removing cream or with soap and water. Do not use solvent. For prolonged irritation, seek medical advice.

In case of accidental eye contamination, wash well with plenty of clean water and seek medical advice.

If swallowed, seek medical attention immediately. Do not induce vomiting.

Do not dispose the material into water or soil. For the sound and valid disposal, consult and follow the related local regulations.



### **White Sand Product Quality**

Ensuring the achievement of customers' requirements and conformance to national and international standards, all WHITE SAND products are developed and manufactured under the base of a highly quality-oriented Product Development processes, and an independently standardized Quality Management System.

# **Technical Support**

WHITE SAND provides technical support to its customers, consultations and technical guidance and assistance in many different applications of construction chemicals, tile adhesives and tile grouts selection, concrete repair systems, and waterproofing systems.

### **Additional White Sand Products**

WHITE SAND produces a wide range of high-quality construction chemicals and specialty products Including following product groups:

- Adhesives and Tiling Systems.
- Surface Treatments and Primers.
- Concrete Repairs and Grouts.
- Waterproofing Systems.
- Finishing Systems.

- Flooring Systems.
- Plasters and Renders.
- Cement Modifiers and Mortar Admixtures.
- Protective Coatings and Linings.

#### Disclaimer

The information given here is based on the best of our knowledge, good faith, experience and laboratory based results and therefore the results will vary depending on the real time application. Also, the values indicated in this Data Sheet here are subject to ± 10% variance due to multiple factors. The performance of our Product depends on the workmanship/quality of application job at the site. Hence White Sand Company for Industry is not responsible for any sort of claims/disputes arising out of any negative results by using our ranges of products. White Sand Company for Industry is not held responsible for use of this product for applications other than specified and/or adopting any faulty application/curing methodologies. It is the user's responsibility to have through this Technical Data Sheet prior to applying our products and to ensure with White Sand Company for Industry that any product information is still prevailing at the time of application. Also the user must be sure that the product is suitable for the use intended and also applied it as specified while taking care of all precautionary measures. While all the products comply with the properties shown on current technical data sheets/brochures, White Sand Company for Industry does not warrant or guarantee the products' performance as it doesn't have any control over factors adopted during its actual application.



