

White sand Primer Sealer

Primer and Sealer for Interior and Exterior Application

Description

WHITE SAND PRIMER SEALER is a high-quality water borne primer based on special acrylic polymer. It has an excellent adhesion and high durability.

Uses and Key functions

Recommended to use for interior and exterior applications on concrete, gypsum, and plastered surfaces in residential, commercial and light industrial applications.

Features and Advantages

- Good penetration behavior to fill the surface porosity and to improve the hiding power of the topcoat.
- Excellent penetration into substrate.
- High resistance to alkalinity & salts.
- High resistance to water.
- Excellent adhesion on substrate and subsequent coats.
- High durability.
- Fast drying.
- Ultra-low VOC and extremely low odor.
- Formulated without formaldehyde, ammonia and APEOs.

Product Performance Properties

Finish	Matt
Color	White
Solid Content (volume)	≈ 24.8 ± 0.5 %
Specific Gravity	≈ 1.35 ± 0.05
Dry Film Thickness (DFT)	50 microns for each coat
Theoretical Coverage Rate*	12 m ² /kg, at 50 microns DFT
Drying time for Recoating	2 hours @ 25 C

* The practical spreading rate of the product depends on the surface, ambient temperature, application method, actual DFT, and the wasted amount.

WHITE SAND

Construction Chemicals

Construct your dream !

Directions for Use

Substrate Preparation

The substrate should sound, clean, and free from dust, oil, grease, and any foreign materials. Fill the holes and cracks with suitable repair compound prior to application of WHITE SAND PRIMER SEALER.

Application Guide

1. The required surface temperature during application must not be less than 10°C; the surface moisture should not exceed 8% and the relative humidity at work place should not exceed 70%.
2. pH of surface should not exceed 9.
3. Paint should be stirred carefully before use.
4. A suitable quantity of "Tap Water" can be added to get reasonable viscosity for application.
5. Do not apply on wet and moistened surfaces until completely dry.
6. Do not apply the next coat unless the previous one is fully dry. Minimum recoating interval time should be followed.
7. Adequate ventilation should be provided during application and drying.

Recommended Thinner

Tap Water.

Cleaning

Clean all tools immediately after job finishing by water. Hardened material will need to be removed mechanically.

Yield/Coverage

The approximate coverage of WHITE SAND PRIMER SEALER is about 12 m²/kg, at 50 microns DFT.

Storage and Shelf Life

WHITE SAND PRIMER SEALER has a minimum 12 months shelf life when stored in dry, shaded place, in unopened, undamaged original packaging. And away from direct sunlight, in ambient temperature below 35 C.

Packaging

- 20 kg plastic pails.

Health and Safety

It is highly recommended to use suitable protective gloves and goggles during handling and application, and to avoid unnecessary direct contact of skin or eyes to the material.

Accidental contact of WHITE SAND PRIMER SEALER to the skin should be washed off immediately with soap and clean water. Eye Irritation or Contact should be washed off immediately with copious amount of clean cold water.

For prolonged irritation, seek medical advice.

WHITE SAND PRIMER SEALER is a non-flammable and not classified as a hazardous material under current legislations.

Do not dispose the material into water or soil.

For the sound and valid disposal, consult and follow the related local regulations.

White Sand Product Quality

Ensuring the achievement of customers' requirements and conformance to national and international standards, all WHITE SAND products are developed and manufactured under the base of a highly quality-oriented Product Development processes, and an independently standardized Quality Management System.

Technical Support

WHITE SAND provides technical support to its customers, consultations and technical guidance and assistance in many different applications of construction chemicals, tile adhesives and tile grouts selection, concrete repair systems, and waterproofing systems.

Additional White Sand Products

WHITE SAND produces a wide range of high-quality construction chemicals and specialty products including following product groups:

- Adhesives and Tiling Systems.
- Surface Treatments and Primers.
- Concrete Repairs and Grouts.
- Waterproofing Systems.
- Finishing Systems.
- Flooring Systems.
- Plasters and Renders.
- Cement Modifiers and Mortar Admixtures.
- Protective Coatings and Linings.

Disclaimer

The information given here is based on the best of our knowledge, good faith, experience and laboratory based results and therefore the results will vary depending on the real time application. Also, the values indicated in this Data Sheet here are subject to $\pm 10\%$ variance due to multiple factors. The performance of our Product depends on the workmanship/quality of application job at the site. Hence White Sand Company for Industry is not responsible for any sort of claims/disputes arising out of any negative results by using our ranges of products. White Sand Company for Industry is not held responsible for use of this product for applications other than specified and/or adopting any faulty application/curing methodologies. It is the user's responsibility to have through this Technical Data Sheet prior to applying our products and to ensure with White Sand Company for Industry that any product information is still prevailing at the time of application. Also the user must be sure that the product is suitable for the use intended and also applied it as specified while taking care of all precautionary measures. While all the products comply with the properties shown on current technical data sheets/brochures, White Sand Company for Industry does not warrant or guarantee the products' performance as it doesn't have any control over factors adopted during its actual application.

