

Technical Data Sheet

White Sand Ultra Seal PU 500

One component, non-sag, elastomeric polyurethane sealant

Product Description

Ultra Seal PU 500 is a one-component, non-sag, polyurethane-based sealant that cures by reacting with air humidity to form a tough and highly elastic low-modulus sealant with a high tear and wear resistance.

Ultra Seal PU 500 is suitable for vertical and horizontal joints, with a wide service temperature range.

Applications and Key Functions

- General sealing of construction and expansion joints.
- Basement walls.
- Precast concrete elements.
- For concrete, wood, marble, stone, aluminum, steel, ceramic, gypsum boards, etc.

Features and Advantages

- One component.
- Excellent adhesion to a wide range of substrates without the need for priming.
- High elasticity and suitable for joints of great mobility.
- Excellent water resistance.
- Suitable for a wide temperature range.
- Very easy and economical to use.
- Excellent aging resistance.
- Paintable, with the usual construction paints.
- Remains elastic at temperatures down to -30°C.
- Good resistance to microorganisms and a variety of chemicals.

Standards

Ultra Seal PU 500 complies with:

- ISO 11600, Type F, Class 25 LM.
- ASTM C920, Type S, Grade NS, Class 25, Use NT, T1, A, M and I.

Product Performance Properties

Type	One-component, polyurethane-based sealant
Color	Various
Density	Non-sag
Consistency	1.18 g/cm ³ approx.
Tack free time (ASTM C679)	1:00 to 3:30 hours @ 23 C, and 50% RH
Elongation at break (ASTM D412)	≥ 800 % @ 7 days
Tensile Strength (ASTM D412)	≥ 1.8 MPa @ 7 days
Adhesion in peel (ASTM C794)	≥ 110 N
Curing rate	≈ 2.5 – 3.5 mm/day
Movement accommodation (ASTM C719)	± 25 %
Application Temperature	5 up to 50 C
Service temperature	-30 up to 90 C
Shore A hardness (ASTM C661)	25± 5 @ 7 days
Effect of heat aging (ASTM C1246)	Pass @ 70 C
Effect of accelerated weathering (ASTM C793)	No cracking
VOC (ASTM D2369)	≤ 75 g/ltr (comply with LEED)

Technical Data Sheet

White Sand Tile Grout

High-Quality Sanded Tile Grout

Directions for Use

Substrate Preparation

All substrates should be clean, dry, and free from dust, oil, grease, and any contaminations that could affect the adhesion.

If the substrates need to be cleaned, use methyl ethyl ketone (MEK), acetone, or grease remover.

Always be sure that the substrates are dry before the application.

Priming

Ultra Seal PU 500 generally has strong adhesion to common clean, dry, and sound substrates without primers. However, suitable primers can be used on porous and non-porous surfaces to achieve optimum adhesion strength. For joints that will be continuously submerged in water, suitable primers should be used.

Using a small brush apply one thin coat at the joint sides and avoid over priming.

Apply Ultra Seal PU 500 sealant while the primer is still tacky to achieve optimum adhesion strength.

Application

The recommended application temperature range is 5oC to 50oC.

For cold weather applications, store the product in a heated area at 20 C for 24 hours before use.

Install a polyethylene joint backing rod to control the sealant depth.

Tooling and finishing should be carried out immediately after the application of the sealant.

For optimum performance, the ratio of width to depth of the sealant should be 2:1. Minimum sealant depth should however be 5 mm.

Limitations

- Not recommended for unsound substrates.
- Although Ultra Seal PU 500 is generally paintable, it is advisable to test for the specific paint for compatibility.
- Long exposure to UV, will reduce surface gloss, but will not affect sealant performance.

Cleaning

Clean tools and equipment first with paper towels and then wipe with Acetone, xylene, or other suitable solvents.

Packaging

Ultra Seal PU 500 is available in 600 ml sausages.

Storage

Ultra Seal PU 500 should be stored in original unopened packages at a temperature of 5 C – 25 C in a dry place.

Shelf Life

Ultra Seal PU 500 has a shelf life of 8 months from the date of manufacturing if stored under the recommended conditions.

Storing the material at temperatures higher than 25 C will shorten the shelf life of the product.

Health and Safety

If Ultra Seal PU 500 comes into contact with the eyes, flush with copious amounts of cold water and obtain medical attention.

The product is non-hazardous once cured.

Consumption in Joints

(Linear meter per 600 ml sausage)

Depth	Width	5 mm	10 mm	15 mm	20 mm	25 mm	35 mm
5 mm		22	11				
7.5 mm				4.9	3.4		
10 mm					2.8	2.2	
15 mm						1.5	1.0

Technical Data Sheet

White Sand Tile Grout

High-Quality Sanded Tile Grout

White Sand Product Quality

Ensuring the achievement of customers' requirements and conformance to national and international standards, all WHITE SAND products are developed and manufactured under the base of highly quality-oriented Product Development processes, and an independently standardized Quality Management System.

Technical Support

WHITE SAND provides technical support to its customers, consultations and technical guidance and assistance in many different applications of construction chemicals, tile adhesives and tile grouts selection, concrete repair systems, and waterproofing systems.

Additional White Sand Products

WHITE SAND produces a wide range of high-quality construction chemicals and specialty products including following product groups:

- Adhesives and Tiling Systems
- Waterproofing and Protective Coating Systems
- Concrete Repair & Restoration Systems
- Finishing & Paints Systems
- Admixtures for Mortar and Concrete
- Surface Treatments and Primers
- Industrial Flooring Systems
- Engineering Grouts and Anchoring Systems
- Resinous Protective Coating and Lining Systems

Disclaimer

The information given here is based on the best of our knowledge, good faith, experience and laboratory based results and therefore the results will vary depending on the real time application. Also, the values indicated in this Data Sheet here are subject to $\pm 10\%$ variance due to multiple factors. The performance of our Product depends on the workmanship/quality of application job at the site. Hence White Sand Company for Industry is not responsible for any sort of claims/disputes arising out of any negative results by using our ranges of products. White Sand Company for Industry is not held responsible for use of this product for applications other than specified and/or adopting any faulty application/curing methodologies. It is the user's responsibility to have through this Technical Data Sheet prior to applying our products and to ensure with White Sand Company for Industry that any product information is still prevailing at the time of application. Also the user must be sure that the product is suitable for the use intended and also applied it as specified while taking care of all precautionary measures. While all the products comply with the properties shown on current technical data sheets/brochures, White Sand Company for Industry does not warrant or guarantee the products' performance as it doesn't have any control over factors adopted during its actual application.



White Sand Co. for Industry

Jeddah, Saudi Arabia

info@whitesand.sa

www.whitesand.sa

