

WHITE SAND MAX PROJECT

High-quality, Polymer-modified cementitious Tile Adhesive for Projects.

Product Description

WHITE SAND MAX PROJECT is a polymer-modified cementitious tile adhesive formulated to be mixed with clean water to provide easy workable thin-bed adhesive. With anti-slip feature. For installation of a wide range of floor and wall ceramic tiles.

WHITE SAND MAX PROJECT is composed of hydraulic binders, selected aggregates, and special polymeric materials and additives.

The raw materials used in manufacturing WHITE SAND MAX PROJECT were carefully selected to enhance the key mechanical properties of the product and provide the most effective application properties.

Features and Advantages

- Good application properties and superior workability.
- Good bond strength.
- Easy tile installation that enables high productivity.
- Slump-free consistency, no sag.
- Used for both floor and wall application.
- Excellent Adhesion to a variety of ceramic tiles and substrates.
- Suitable for internal Applications.

Standard compliance

WHITE SAND MAX PROJECT complies with EN 12004 as C1T.

WHITE SAND MAX PROJECT conforms to SASO GSO 12004, class C1T.

Product Performance Properties

Type	Pre-mixed cementitious powder
Color	White and Grey
Mixing Water	≈ 10 - 11 kg per 50 kg bag
Wet Density	≈ 1.45 kg/l
Pot Life	90 minutes
Open time	20 minutes
Adjustability	10 – 15 minutes
Tensile adhesion strength (EN 1348)	≥ 0.5 MPa (after 28 days)
Shore "D" Hardness	≥ 55
Compressive Strength (ASTM C109)	7.5 N/mm ² (@28 days)
Flexural Strength (ASTM C348)	2.6 N/mm ² (@28 days)
VOC Content	< 25 g/liter
Set time: 24 hours 48 hours 14 days	Ready for grouting Ready for light traffic Ready for heavy traffic

* Values are valid at ambient temperature of 23 C, and 55% Relative Humidity.

Directions for Use

Substrate Preparation

All surfaces must be clean, sound and free from any loosely adhering particles. Cement laitance must be removed. Wire brush, sand- or water-blast or grinding may be used to clean the substrate. Concrete substrates must be at least 4 weeks old depending on climate. Wet all surface (except gypsum board) with clean water before application of WHITE SAND MAX PROJECT. The surface should appear damp with no water pooling.

Mixing

WHITE SAND MAX PROJECT should be added slowly to about 4.4 liters of clean water during mixing. It is recommended to use a mixing paddle attached to a slow speed electric drill for at least 2 minutes until the material becomes smooth in consistency and slump-free. Allow the material to saturate for 5 – 10 minutes before use. Do not add water to the adhesive mortar mixture once the mixture starts to harden.

Application

trowel and then combed through a suitably sized notched trowel in straight ribs to give ribbed adhesive bed. Spread the mortar adhesive to an area that can be tiled within 10 – 15 minutes. After applying the adhesive and within the open time, bed and press the tiles firmly with a slight twisting action to ensuring that the tile back achieves full contact with the adhesive. immediately knock the tiles to the desired position. And if required, adjust the position within its adjustability time of 10 – 15 minutes after installation. Use the correct cross spacer to control joints. Ensure that there are no voids under the tiles and they are fully supported by the adhesive. Clean off excess adhesive from the tile face and the grout lines with a damp cloth before it sets. Allow the installed tiles to remain undisturbed for at least 48 hours. Mortar adhesive must not rise between the tile joints higher than halfway the thickness of the tiles. It is recommended to use WHITE SAND TILE GROUT to fill the joint gaps after 2 days of tile installation

Cleaning

Clean all tools immediately after job finishing with water. Hardened material will need to be removed mechanically.

Packaging

50kg paper bags.

Yield and Coverage

Coverage of 50 kg bag of WHITE SAND MAX PROJECT mixed with 10.5 kg of clean water is 11.5 – 14 m². This stated data is approximate and is for general guidance only. Actual consumption depends on the nature of the substrate, method of application, and wastage of material.

Storage and Shelf Life

WHITE SAND MAX PROJECT has a minimum 12 months shelf life when stored in dry, shaded place. In unopened, undamaged original bag. And away from direct sunlight in ambient temperature below 35 C.

Health and Safety

It is highly recommended to use suitable protective gloves and goggles during handling and application, and to avoid unnecessary direct contact of skin or eyes to the material.

Accidental contact of WHITE SAND MAX PROJECT to the skin should be washed off immediately with soap and clean water. Eye Irritation or Contact should be washed off immediately with copious amount of clean cold water.

For prolonged irritation, seek medical advice.

WHITE SAND MAX PROJECT is a non-flammable and not classified as a hazardous material under current legislations.

Do not dispose the material into water or soil. For the sound and valid disposal, consult and follow the related local regulations.

White Sand Product Quality

Ensuring the achievement of customers' requirements and conformance to national and international standards, all WHITE SAND products are developed and manufactured under the base of a highly quality-oriented Product Development processes, and an independently standardized Quality Management System

Technical Support

WHITE SAND provides assistance to its customers and gives site support, consultations and technical advice on concrete repair, surface preparation and treatment, tile adhesive and tile grout selection, tile installation techniques and maintenance of different types of tiles.

Additional White Sand Products

WHITE SAND produces a wide range of high-quality construction chemicals and specialty products Including following product groups:

- Adhesives and Tiling Systems.
- Surface Treatments and Primers.
- Concrete Repairs and Grouts.
- Waterproofing Systems.
- Finishing Systems.
- Flooring Systems.
- Plasters and Renders.
- Cement Modifiers and Mortar Admixtures.
- Protective Coatings and Linings.

Disclaimer

The information given here is based on the best of our knowledge, good faith, experience and laboratory based results and therefore the results will vary depending on the real time application. Also, the values indicated in this Data Sheet here are subject to $\pm 10\%$ variance due to multiple factors. The performance of our Product depends on the workmanship/quality of application job at the site. Hence White Sand Company for Industry is not responsible for any sort of claims/disputes arising out of any negative results by using our ranges of products. White Sand Company for Industry is not held responsible for use of this product for applications other than specified and/or adopting any faulty application/curing methodologies. It is the user's responsibility to have through this Technical Data Sheet prior to applying our products and to ensure with White Sand Company for Industry that any product information is still prevailing at the time of application. Also the user must be sure that the product is suitable for the use intended and also applied it as specified while taking care of all precautionary measures. While all the products comply with the properties shown on current technical data sheets/brochures, White Sand Company for Industry does not warrant or guarantee the products' performance as it doesn't have any control over factors adopted during its actual application.

